

steering tube facing the rider. \*The VIN Plate is located at the bottom of steering tube facing the rider. The Engine# is located under the crankcase\*

15. Unlock the gas tank fill the gas tank with  $\frac{1}{4}$  Gallon of 87 unleaded fuel. \*Do not mix with oil!! This is not a 2-Stroke vehicle!!\*

16. Turn the Key to ON position on the ignition.

17. Stand on the left side of the vehicle. Hold the left brake with your left hand firmly. Press downwards on the rear portion of the seat with your right hand. Force the vehicle to tilt downwards.

18. Place your right foot on the kick starter firmly. Kick downwards and towards the front. You should not hear any loud cracking noise but rather a low toned noise.

19. Continue kicking until the vehicle starts. Once it starts let the vehicle to warm-up for 10 minutes then shutdown.

20. Now open the trunk again and lock the carburetor cover with the screw driver.

21. Mount the Rear trunk. Mountain equipment should be located in the Trunk.

22. Open the battery compartment right under where your feet would be when riding the vehicle.

23. Insert the battery and connect the wires. Black is ground. Red is Positive. Green is Ground. Fasten securely and close the battery compartment.

24. Now turn your key to ON position and hold the left brake lever with your left hand, press the ignition button with your right hand. Once warmed up for another 10 minutes, test ride. During break in periods do not go faster than 30mph. Make sure to wear all proper safety equipment when riding. Do not carry a passenger. Please follow maintenance instructions.